

RIEZLER

Control unit

MSE-300

Article-No. 5-0037-001



Technical data

Features	High-definition, daylight-suitable TFT display, integrated MPEG-4 video recorder, integrated meter counter with textgenerator, Li-Ion battery pack
Screen size	8 inch
Resolution	800 x 600
Pan and tilt camera controls	✓
Crawler controls	✗
Storage	SD card (up to 32 GB)
Video format	MPEG-4 with single frame function
Software	✗
Sensor data overlay	pan and tilt angle in degrees, internal pressure in bar (alarm function when threshold is exceeded)
Battery	2 Li-Ion battery with a battery charger and charge indicator
Power supply	12 - 24 V DC via external power supply (100 - 240 V AC), 12 V jack for car operation
Microphone jack for voice recording	✓
Interfaces	1 x BNC Video-IN, 1 x BNC Video-OUT, RS-232 for data transfer to a capture program (optional)
IP protection class	IP 54
Operating temperature	0° to 40° C 32° to 104° F
Storage temperature	0° to 40° C 32° to 104° F
Material	plastic / aluminium
Dimensions (L x W x H)	350 x 190 x 315 mm 13.8 x 7.5 x 12.4 in
Weight	ca. 4.5 kg 9.9 lbs

Proudly distributed by



5 Avian St, Kunda Park QLD 4556.

Marshall Horne 0409 850 577

mh@drainchem.com.au | www.drainchem.com.au

Drainchem A.B.N 15 165 891 985