

RIEZLER

Pan and tilt camera

RSK-78

Article-No. 5-0033-001 (PAL)

Article-No. 5-0033-002 (NTSC)



Technical data

Application area	DN 70 - DN 300
Suitable for 87° bends	from DN 100
Swivel range	± 115°
Rotation range	infinite
Push operation	✓
Crawler operation	✓
Waterproof	✓ up to 10 bar (static pressure)
Lighting	18 LEDs
Lens	85°
Zoom	✗
Focus	manual (1 cm - ∞ 0.4 in - ∞)
High-resolution color camera module	700 lines
Image sensor	1/2.8" Color-CMOS
Upright picture	automatic horizont compensation
Parallel laser	✗
Distance laser points	✗
Internal pressure-supervision	✓
Pan / rotation angle	✓
Rotation angle vertical	✗
Pluggable mounting	✓
Operating temperature	0° to 60° C 32° to 140° F
Storage temperature	-10° to 60° C 14° to 140° F
Material	aluminium / stainless steel
Dimensions (Ø / Length)	60 / 100 mm 2.4 / 3.9 in
Weight	ca. 680 g 1.5 lbs

Proudly distributed by



5 Avian St, Kunda Park QLD 4556.

Marshall Horne 0409 850 577

mh@drainchem.com.au | www.drainchem.com.au

Drainchem A.B.N 15 165 891 985